

# SK-NM10,NM30

## Megapixel H.264 IP NETWORK IR Mini Outdoor Dome Camera

Model No.	SK-NM10	SK-NM30
Camera		
Type	Megapixel Network Day & Night IR Camera	
Image sensor	1/3" PROGRESSIVE SCAN CMOS	1/3" PROGRESSIVE SCAN CMOS
Min. illumination	0.1 lux@F1.2, AGC on 0 lux with IR	
Shutter time	1/25s~1/100,000s	
Lens	4mm@F2.0, angle of view. 75.8°	
Lens mount	M12	
Angle adjustment	PAN: 0°~355°, TILT: 0°~65°	
Digital noise reduction	3D DNR	
Wide dynamic range	Digital WDR	
Day & Night	ICR	
Compression standard		
Video compression	H.264 / MJPEG	
H.264 codec profile	Main profile	
Bit rate	32 Kbps~16Mbps	
Dual stream	Yes	
Image		
Max. image resolution	1280 x 960	2048 x 1536
Frame rate	50Hz:25fps (2180x960), 25fps (1280x720), 60Hz:30fps (1280x960), 30fps (1280x720)	50Hz: 12.5fps (2048 x 1536), 25fps (1920 x 1080), 25fps (1280 x 720) 60Hz: 15fps (2048 x 1536), 30fps (1920 x 1080) 30fps (1280 x 720)
Image settings	Saturation, brightness, contrast adjustable through client software or web browser	
BLC	Yes, zone configurable	
Network		
Alarm trigger	Motion detection, tampering alarm	
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP	
System compatibility	ONVIF, CGI	
General functionalities	User authentication	
Interface		
Communication interface	1 RJ45 10M/100M Ethernet port	
General		
Operating conditions	-40°C~60°C (22°F~140°F) humidity 95% or less (non-condensing)	
Power supply	12 VDC ±10%, PoE (802.3af)	
Power consumption	MAX.5W(7W with ICR on)	
Impact protection	IEC60068-275Eh, 50J; EN50102, up to IK10	
Ingress protection	IP66	
IR range	Approx 20 to 30 meters	
Dimensions	Φ 111 x 82 mm	
weight	500g	

